



# RIDE RING LINEAR S

675-30701102305d

RIDE RING SYSTEM LINEAR SYSTEM LUMINAIRE made of die-cast aluminium, white, similar to RAL 9016, satined PMMA diffuser for homogeneous illumination light output direct, with converter, max. 500mA, dimmability: DALI, IP20




## DRAWING



## TECHNICAL DETAILS

System perform. [W]	15
Bulb type	LED
Luminous flux [lm]	1230
Current sec. [mA]	500
Colour temp. [K]	2700K
CRI	>90
Optics	PMMA opal diffuser flat
Designer	INHOUSE
Converter	with converter
Light output	direct
Voltage [V]	220-240V 50/60Hz
Material	die-cast aluminium
Length [mm]	842
Width [mm]	35
Height [mm]	35
IP protection class	IP20
Voltage class	protection cl. I
Net weight [kg]	2,10
Color lamp	white
RAL	9016
EAN-Number	9008905919619
Lifetime [h]	L80 B10 50 000
No. of luminaires B16A	50

## LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.